



# MATERIAL SAFETY DATA SHEET

## GENERAL CT (58)

Hazardous according to criteria of Worksafe Australia

### FMP Group (Australia) Pty. Ltd.

Elizabeth Street P.O.Box 631  
Ballarat Ballarat  
Phone 03 5327 0211

---

#### IDENTIFICATION

**Shipping Name** GENERAL CT (58)  
**Product Use** Friction Material for vehicle brakes  
**UN Number** Not Available  
**Dangerous Goods** 0  
**Packaging Group**  
**Subsidiary Risk** 0  
**HAZCHEM Code**

---

#### PHYSICAL DESCRIPTION / PROPERTIES

**Appearance** Solid, dark grey in colour  
**Boiling Point** not relevant  
**Melting Point** not relevant  
**Vapour Pressure** not relevant  
**Specific Gravity** 1.7 - 2.5  
**Flash Point** not relevant  
**Flammability Limits** not considered a significant fire risk however the friction material will burn  
**Solubility** insoluble  
**Decomposition Temperature** unknown

#### FIRE AND EXPLOSION HAZARD DATA

##### Extinguishing Media

Carbon dioxide, water, foam

##### Special Fire Fighting Procedures

Combustion products of this material may be toxic. Use a self-contained breathing apparatus when fighting fires involving chemical products

##### Unusual Fire and Explosion Hazards

None known

#### REACTIVITY DATA

**Stability** Yes  
**Conditions to avoid** Not applicable  
**Materials to avoid** Strong oxidizing agents

##### Hazardous decomposition products

Airborne fibrous dust, incomplete combustion. May create toxic fumes

**Hazardous polymer occurrence** No

---

**INGREDIENTS**

---

<b>CHEMICAL</b>	<b>CAS#</b>	<b>UN#</b>	<b>Approx. Proportion</b>	<b>Worksafe Australia Exposure Std 8hr TWA</b>
Lime	1305-62-0		3%	5mg/m3
Resin	9003-35-4		7%	
Graphite	7782-42-5		3%	3mg/m3
Mineral Fibre		1373	7%	0.5fibres/mL
Antimony Trisulphide	1345-04-6	1549	3%	0.5 mg/m3
Other Ingredients Determined Not To Be Hazardous			to 100%	

---

---

**Ingredient: SYNTHETIC MINERAL FIBRES**

Exposure Standard (Worksafe Australia) 0.5 fibre/mL

A person should not smoke in an area where atmospheric fibres may be present.

Information and training. Any person carrying out work involving handling fibrous materials must receive adequate training, which will enable them to carry out their respective tasks in a safe manner and without risk to the health and safety of other persons.

---

**Ingredient: TITANIUM STRIPE**

This ingredient contains less than 0.001% ammonium dichromate and less than 0.05% carbon black by product weight.

**Further Information** Normal use of this product may liberate dust. Avoid inhalation of dust.

---

## HEALTH HAZARD DATA

---

<b>LD50-LC50 Mixture</b>	Not established
<b>Route of Entry - Ingestion</b>	May cause gastric irritation
<b>Route of Entry - Eyes</b>	May cause irritation
<b>Route of Entry - Skin</b>	Prolonged skin contact may result in skin irritation or contact dermatitis
<b>Route of Entry - Inhalation</b>	Respiratory tract effects include coughing, wheezing, shortness of breath

### HEALTH HAZARD ACUTE AND CHRONIC

Exposure to dusts of silica, talc, graphite, carbon & coal can lead to chronic lung diseases such as pneumoconiosis. In severe cases these diseases can be fatal. Exposure to these dusts may also lead to non-disabling conditions known as pleural thickening, plaques & calcification.

### CARCINOGENICITY

Not Applicable

### SIGNS/SYMPTOMS OF OVEREXPOSURE

Respiratory irritation, asthma-like symptoms and discomfort while breathing.

### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Persons with pre-existing respiratory disease may be at increased risk from exposure to airborne fibres, dusts and vapours.

### SENSITIZERS

Not Applicable

---

## EMERGENCY/FIRST AID PROCEDURES

---

- Inhalation: remove to fresh air. Obtain medical attention
- Skin: wash exposed area with soap and water. Obtain medical advice if irritation develops
- Eyes: flush with large amounts of water for at least 15 minutes, keep eyelids open. Obtain medical attention
- Ingestion: obtain medical attention as a precautionary measure.
- Other: clothing contaminated with fibrous dust should be isolated in the work area until laundered.
- Avoid contamination with other areas

---

## PRECAUTIONS FOR SAFE HANDLING AND USE

---

- Do not breathe fibrous dust
- Precautions-Handling/Storing: Do not clean parts with compressed air. Avoid scraping or scratching brake linings or otherwise creating dust during assembly
- Isolate brake-servicing areas if possible
- Local exhaust ventilation is recommended
- Clean brake parts with a vacuum fitted with a HEPA filter
- Wipe with damp rags to remove residue containing fibrous dusts
- Dispose of used rags while still wet into sealed bags
- Waste Disposal Method: handle used parts so as to avoid creating airborne dust. Place used parts in an airtight container, label and dispose in a licensed landfill in compliance with local, state and federal regulations
- Moulded friction linings only release fibres when in service or when abraded
- Isolate and launder contaminated clothing before reuse

---

## CONTROL MEASURES

---

- Respiratory Protection: Exposure to airborne fibres and/or dusts shall not exceed the exposure standard. If the exposure standard is exceeded a suitable particulate respirator must be worn and the wearer trained in the fitting and use thereof
- Ventilation: Use adequate mechanical ventilation. Local exhaust may be required for enclosed operations
- Protective Gloves: Protective gloves are recommended
- Eye Protection: Safety glasses with side shields or goggles
- Other Equipment: Not required under normal use
- Work Hygienic Practices: Wash thoroughly after handling and before eating, drinking or smoking
- Safety and Health Data: Workers exposed to fibrous dust shall be trained as to its potential hazards and the means of reducing those hazards
- Other Control Measures: Not required under normal use

---

## STORAGE AND TRANSPORT

---

Individual friction material components should be stored and transported in accordance with the Dangerous Goods Regulations and Occupational Health and Safety Regulations as applicable in the relevant state, territory or country, or in accordance with the manufacturers MSDS. Labelling and packaging should be in accordance with the relevant applicable Regulations or in accordance with the manufacturers recommendations.

---

## SPILLS AND DISPOSAL

---

All spillages of friction material should be vacuumed up using an industrial vacuum cleaner fitted with a high efficiency particulate (HEPA) filter. Spilled material should be placed in a suitable sealed and appropriately labelled container ready for disposal.

---

## FIRE AND EXPLOSION HAZARD

---

Hazardous decomposition products from heating and burning may include:

- Carbon monoxide
- Carbon dioxide
- Oxides of nitrogen

---

## LABEL DATA

---

### RISK Phrases

- R38 Irritating to skin.
- R37 Irritating to respiratory system.
- R20 Harmful by inhalation.

### SAFETY Phrases

- S51 Use only in well ventilated areas.
- S56 Dispose of this material and its container at hazardous or special waste collection point.

---

## SPECIAL HAZARD PRECAUTIONS

---

Not Applicable

---

## CONTACT POINT

---

- Occupational Health and Safety Officer Phone 03 5327 0211
- Product Development Manager Phone 03 5327 0211

---

## DISCLAIMER

---

While every effort has been made to ensure the accuracy of the information, the information is based on data believed by FMP Group (Australia) Pty. Ltd. to be accurate at the time of writing this Material Safety Data Sheet, but is subject to change without notice. Exact formulations are proprietary and therefore confidential. Precise product composition will not be disclosed except as in accordance with relevant laws and regulations. The information is given in good faith but FMP Group (Australia) Pty. Ltd. gives no warranty, expressed or implied of any kind whatsoever as to its accuracy, completeness or otherwise.

Under no circumstances shall FMP Group (Australia) Pty. Ltd. Be responsible for damages of any nature, directly or indirectly arising out of materials referred to, or the publication use or reliance upon the data provided.